2205 Baler Valve Bypass

	Remove access panel on the side of the baler. You willneed tamper proof torx bit TX30 (Torx Security Tool)
	Locate the Top port on the bottom valve
	Disconnect hose from top port and pivot hose up to top cylinder. The elbow is on a swivel

Mil-tek USA ▪ 10 Export Dr. ▪ Sterling, VA 20164 ▪ T. (877) 664-5835 ▪ F. (571) 267-7449
miltek@miltekusa.com ▪ www.miltekusa.com
© This document is property of Mil-tek USA and is only to be used for internal purposes within the worldwide Mil-tek organization and may NOT by any means be passed on to any third party.

2205 Baler Valve Bypass

	Disconnect current black hose going to top cylinder and connect bottom valve hose directly to the top valve port.
	You can now use the "lockout"as a bypass to access the valves underneath the plate with ease. The valves underneath the plate will have no air on them and we can service them. Will need to dismount this valve in order to access the valve bolts. Access port is behind this orange valve.

Mil-tek USA ▪ 10 Export Dr. ▪ Sterling, VA 20164 ▪ T. (877) 664-5835 ▪ F. (571) 267-7449
miltek@miltekusa.com ▪ www.miltekusa.com

© This document is property of Mil-tek USA and is only to be used for internal purposes within the worldwide Mil-tek organization and may NOT by any means be passed on to any third party.